

	3' x 7' (1 x 2 m)	7' x 7' (2 x 2 m)	10' x 7' (3 x 2 m)	13' x 7' (4 x 2 m)	17' x 7' (5 x 2 m)	20' x 7' (6 x 2 m)
Total Width ext./int.	82.70 in. / 77.75 in.	82.70 in. / 77.75 in.	82.70 in. / 77.75 in.	82.70 in. / 77.75 in.	82.70 in. / 77.75 in.	82.70 in. / 77.75 in.
Total Depth ext./int.	43.30 in. / 38.40 in.	82.70 in. / 77.75 in.	122.05 in. / 117.10 in.	161.40 in. / 156.50 in.	200.80 in. / 195.85 in.	240.15 in. / 235.30 in.
Total Height ext./int.	82.70 in. / 76.15 in.	82.70 in. / 76.15 in.	82.70 in. / 76.15 in.	82.70 in. / 76.15 in.	82.70 in. / 76.15 in.	82.70 in. / 76.15 in.
Weight (lbs.)	480 lbs	700 lbs	900 lbs	1,070 lbs	1,400 lbs	1,650 lbs



BOS CS have serviced clients both in government organizations and municipalities, as well as in the private sector such as oil and gas, airlines, construction, remediation, storage, shipping and general industries.

Our units are manufactured with the highest of standards with strong emphasis on safety. The materials have been chosen to fit the themes of durability, ability to recycle, and easy to handle.

# BOS<sub>CS</sub>

[info@boscs-usa.com](mailto:info@boscs-usa.com)

[www.boscs-usa.com](http://www.boscs-usa.com)

+1 (844) BOS-3757



## BOS<sub>CS</sub> QB Container



[www.boscs-usa.com/containers](http://www.boscs-usa.com/containers)





Made with German technology for over 40 years.

Made of 20 gauge (0.8 mm) recycled galvanized steel.

Easy to assemble and knock down. No tools required.

Robust structure with:

Wind load 100 mph (160 km/h).

Snow load 43 lbs/ft<sup>2</sup> (210 kg/m<sup>2</sup>).

Floor load 100 lbs/ft<sup>2</sup> (500 kg/m<sup>2</sup>).

Ability to connect with no walls in the middle:

End-to-end - any 2 units.

Side-by-side - 10ft, 13ft, or 17ft with up to three units

Ability to lift loaded units:

With forklift up to 4,000 lbs (2 tons).

With crane up to 6,600. Lbs (3 tons).

Ability to stack fully loaded units:

Up to 2 units outdoors.

Up to 3 units indoors.

